



TECHNICAL DATA

PRODUCT

CLASSIC COLOUR

DESCRIPTION

An Acrylic Glaze, which when coloured with vinyl emulsion/satin latex produces semi transparent coloured effects.

APPLICATION

Seal porous surfaces. Ensure Classic Colour is well mixed

Choose the base coat colour and the colour of the Classic Colour effect. Apply the base coat in vinyl silk emulsion/satin latex and allow to dry. The second coat is preferably matt emulsion (satin can be used) in the selected colour mixed with Classic Colour as follows:

Warm Conditions/low humidity: (above 20°C/70°F) – six parts Classic Colour – one part emulsion/latex.

Cool conditions/high humidity: (below 20°C/70°F) – four parts Classic Colour – one part emulsion/latex.

Ratios may be varied to suit application conditions and changes in temperature/humidity.

Brush the mixture liberally over the base coat. Large areas such as walls should be divided into sections to keep a workable edge.

USES

Walls, doors, furniture, cabinets, wood trim.

COVERAGE

Approx. 10-20 sq. m per litre. 108-215 sq. ft per US qt

SHEEN LEVEL

As vinyl emulsion/satin latex.

CONTAINERS

500ml, 1L, 2L, 4L. US pint, US Quart, US gal.

No OF COATS

As required for effect

WORKING TIME

Up to one hour.

DRYING TIME

Classic Colour – up to 24 hours. Base Coat – a minimum of 24 hours with ventilation.

Low temperature/high humidity increases drying time. Air movement is essential for faster drying

RECOAT TIME

Minimum 24 hours. Test before applying further coats or applying protective varnish.

CURING

Minimum of 5 days depending on environment.

CLEANING

Clean tools/equipment with warm soapy water, rinse well with clean water, and allow to dry naturally.

FLAMMABILITY No fire hazard before or during use, or in the cured state.

STORAGE Protect from extremes of temperature during storage and application.

HEALTH SAFETY AND THE ENVIROMENT

Non-hazardous. Ensure good ventilation. Keep out of reach of children. Contact with eyes-wash immediately with warm water. Remove excess from tools and mixing vessels before washing in warm soapy water. Do not empty containers into drains or watercourses.

The information supplied herein is accurate to the best of our knowledge. Since conditions and methods are beyond our control, no warranty is expressed or implied. You are advised to assess the suitability of the product on a test area before application

Further information may be obtained from:

POLYVINE LIMITED

Vine House
Cheddar Business Park
Wedmore Rd.
Cheddar BS27 3EB
United Kingdom

Telephone No.	0845 017 1671
International	+44 845 017 1671
Fax:	0845 017 1672
Email	info@polyvine.co.uk

MATERIAL SAFETY DATA SHEET

1. IDENTIFICATION OF PRODUCT AND COMPANY

PRODUCT **CLASSIC COLOUR**

COMPANY: Polyvine Limited, Vine House, Cheddar Business Park, Wedmore Rd. Cheddar BS27 3EB UK
Emergency Telephone 0845 017 1671 International +44 845 017 1671

2. COMPOSITION

Water based dispersion of methacrylic esters, with no hazard classification

Chemical characterisation: Acrylic

CAS N o: Names: Conc.

3. HAZARDS IDENTIFICATION

On available data this product has no hazard classification according to 88/379/EEC.

4. FIRST AID MEASURES

GENERAL: Immediately remove all contaminated clothing. In all cases of doubt, or when symptoms persist, seek proper medical attention. Never give anything by mouth to an unconscious person.

INHALATION: Remove to fresh air, keep patient warm and at rest if breathing is irregular or stopped, administer artificial respiration. Giving nothing by mouth. If unconscious place in recovery position and seek medical advice.

EYE CONTACT: Holding eyelids apart, flush copiously with clean, fresh water for at least 10 minutes and seek medical advice.

SKIN CONTACT: Remove contaminated clothing. Wash skin thoroughly with soap and water or use recognised skin cleaner.

DO NOT use solvents or thinners.

INGESTION: If accidentally swallowed obtain medical attention. Keep at rest. DO NOT induce vomiting.

5. FIRE-FIGHTING MEASURES

Aqueous dispersions will not burn. Dried films are combustible and may emit noxious fumes. Water, foam, carbon dioxide or dry powder extinguishers are all suitable. Wear breathing apparatus.

6. ACCIDENTAL RELEASE MEASURES

Spillage should not be washed into any drain. Spillage should be soaked up with an inert absorbent (e.g. sand) for disposal.

7. HANDLING AND STORAGE

HANDLING

This product should be handled in accordance with good safety and hygiene practices. Small levels of volatile organic compounds may accumulate in the headspace of containers, which should be opened in ventilated surroundings.

STORAGE Sealed containers should be stored between 5 C and 40C. Bulk tanks should be externally vented.

8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

EXPOSURE CONTROLS

Local exhaust ventilation may be required in circumstances where the product is sprayed, heated or dried.

PERSONAL PROTECTION

Respiratory	-	Masks, when spraying
Hand	-	Gloves, if risk of skin contact
Eye	-	Goggles, if risk of splashing
Skin	-	Standard industrial overalls if splashing
O.E.L.		

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	-	Milky liquid
Odour	-	Mild
PH	-	8.0
Boiling point	-	Approx. 100C (as water)
Flammability and Autoignition temp		N/A
Vapour pressure	-	23 mbar as water
Water solubility	-	Fully miscible
Relative density	-	Approx. 1.03 at 20 C (ISO 8962)

10. STABILITY AND REACTIVITY

This product is stable under normal conditions of use.

11. TOXICOLOGICAL INFORMATION

INHALATION - May be irritating to respiratory system

INGESTION - May be harmful if swallowed

SKIN CONTACT- may cause skin irritation

LONG TERM EXPOSURE - No information available

12. ECOLOGICAL INFORMATION

Do not empty into waters and drains.

13. DISPOSAL INFORMATION

Product recommendation: Do not allow into drains or watercourses.

Empty containers are to be disposed according to official rules.

Contaminated packaging recommendation: Contaminated packaging must be emptied of all residues and, following appropriate cleaning, may be sent to approved recycling plant. Uncleaned packaging must be disposed of in the same manner as the medium.

14. TRANSPORT INFORMATION

This product is not classified hazardous for transportation.

15. REGULATORY INFORMATION

EEC Hazard Classification - None

The product contains only substances, which are on the European Inventory of Existing Chemical Substances (EINECS).

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is based on data provided by sources considered to be reliable. This data is intended to enable safety assessment to be made and should not be construed as guaranteeing specific properties. Users are recommended to consult technical information sheets for advice on specific applications.

Further information may be obtained from:

POLYVINE LIMITED

Vine House
Cheddar Business Park
Wedmore Rd.
Cheddar BS27 3EB
United Kingdom

Telephone No.	0845 017 1671
International	+44 845 017 1671
Fax:	0845 017 1670
Email	info@polyvine.co.uk

Date of issue: October 2014