



Whitson's Superior Adhesion Primer

Whitson's Superior Adhesion Primer is very binder rich, water based bridging primer made from soya alkyd (a natural product) and was formulated originally as a factory finished kitchen and cabinetry refurbishment product. We asked our chemist and manufacturer to come up with a paint that had high adhesion to 2 pack AC and precat sprayed products and also have great adhesion to aged alkyd and polyurethane products i.e. oil gloss, oil eggshell and polyurethane varnish of all sheens.

Field testing by painters and decorators has helped us to improve the paint dramatically and we now have improved adhesion for tiles, plastic, foil wraps and melamine. Please note that Whitson's Superior Adhesion Primer has no special stain blocking abilities. With furniture it is perfect for modern high lacquer, veneered or slick surfaces like Ikea furniture but is not suitable for waxed surfaces – all wax must be removed. You can use any decorative paint over the top.

It is advised that a small test area is tried first if there is any doubt about the suitability of the surface you are applying to.



Preparation

Remove all loose or flaking material. Ensure the surface is dry and free from dirt, grease and other contaminants.

As a bridging primer, this product is designed to only be used on existing sealed or painted interior surfaces.

Application

Do not apply in very humid conditions or where temperatures are below 5°C or above 30°C. Stir well before use.

Suitable for application by brush, roller and spray. Ensure that the paint is applied in a uniform coat and spread at a film thickness that yields a coverage rate of approximately 10m² per litre.

Drying

Allow to dry for 3-4 hours before touch up or overcoating. Full hardness and durability of the coating will develop over several days. Please note that drying will be noticeably slower at temperatures below 12°C.

Cleaning

Remove as much paint as possible from all equipment and then clean thoroughly in cold water.

Storage

Ensure containers are sealed, and then store in dry conditions between 5°C and 30°C. Protect from frost.

Health, Safety & Environmental

This is a water based paint. Ensure good ventilation during application and drying. Avoid contact with eyes and skin. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. In case of contact with skin, wash immediately with plenty of soap and water (do not use any solvents). When sanding avoid inhalation of dust and wear a suitable face mask. Do not empty into drains or watercourses. Many local authorities have facilities for the disposal of waste paint. Dispose of empty containers in accordance with local regulations. Keep out of reach of children.

Directive 2004/42/EC VOC limit for this product (category A/i): 140g/litre (2010)

This product contains a maximum of 27g/litre VOC